

### Features & Benefits

- weather resistant U.L. V94 rated plastic housing
- available in 6, 10, 12 and 25 pair configuration
- termination options available in IDC (66 clip) and bix block
- may be utilized in place of network interface device
- eliminates requirement for internal closet space
- security fasteners restrict access to authorized personnel only



3006QCP

Outdoor

## 3000P Series Ordering Information

Model No.	Order No.	Pair Count	Input	Output	Dimensions (H" x W" x D")	Weight (lbs)
3006QC2P	909002	6	66 block	66 block	7.9 x 7.5 x 3.35	2.0
3010QC2P	909004	10	66 block	66 block	15 x 9.85 x 4.65	2.5
3012QC2P	909003	12	66 block	66 block	15 x 9.85 x 4.65	3.0
3025QC2P	909005	25	66 block	66 block	15 x 9.85 x 4.65	8.5
3006BP	909008	6	bix connector	bix connector	7.9 x 7.5 x 3.35	3.5
3010BP	909006	10	bix connector	bix connector	15 x 9.85 x 4.65	5.5
3012BP	909001	12	bix connector	bix connector	15 x 9.85 x 4.65	6.0
3025BP	909007	25	bix connector	bix connector	15 x 9.85 x 4.65	8.5

Note: Protection modules ordered separately.



## Building Entrance Terminals (Outdoor)

Outdoor